PureWaterCooler

Hot & Cold Countertop water dispenser

Bottle-less water cooler is great for small offices and break rooms. Order optional filter pack or provide you own source of filtered water.

Standard Features

- 2 Temp: Cold: 37-50° F, Adjustable Hot: 180° F, Autocontrol
- LED indicator for hot and cold water on the front panel
- Individual on/off switches for hot or cold function on rear panel
- Completely sealed stainless steel cold reservoir and hot tank
- Convenient, enclosed, no-drip dispensing faucets
- Type 304 stainless steel hot and cold water tanks
- High efficiency sealed compressor cooling system with adjustable cold water thermostat, 37-50°F
- Safety lock for hot water faucet

Optional Add-On Filter Pack

Attaches to back of Cooler

- 2 Filtration Options: 2-stage standard filtration takes out sediment, chlorine taste and odor 3-stage adds 50 GPD Reverse Osmosis membrane to remove contaminants
- Adds only 4.5" to cooler depth



Filter Pack installs easily with 4 screws 2-stage, standard filtration shown



Executive Gray option

Specifications

Voltage: 115 VAC

Cold tank volume 1 gal Hot tank volume .5 gal

Weight: 45 lb.

Filter System

Standard Filter 500/FP Stage 1: 5 micron Sediment

Stage 2: 10 micron Activated Carbon

Reverse Osmosis Filter 500/FPR

Above 2 stages plus

Stage 3: 50-GPD RO Membrane

Meets Energy Star Requirements



PWC-500

ORDERING INFORMATION

Dimension: 13" W x 15" D x 19.5" H

Cooling Rate: 1.5 gal/hr 37-50 °F

Heating Rate: 1.3 gal/hr 180 °F

Power Required: 600w max

2-Temp Hot and Cold Dispenser Add-on filter pack - 50 GPD Reverse Osmosis membrane

Add-on filter pack - Standard Filtration

Executive Gray Cabinet

Replacement Filters Sediment

GAC Carbon

RO membrane, 50 GPD



PWC-500

add /FPR

add /FP

add /EG

IFA-4035

IFA-4034

MA-4203





